

Product data sheet


EPK L80 LE3 ***
 ECOPAK EMERGENCY
 DEXTRA



IP
20


Ecopak - 1500mm, Surface mounted batten luminaire, White powder painted metal body and steel spine, injection moulded polycarbonate end caps, high transmission curved opal diffuser. Options: LE3 - Lithium Emergency (427 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) ** Select sensor R21E - Reacta 21, On/Off R21C - Reacta 21, Corridor Mode* R44 - Daylight regulating and Occupancy Sensor RLS - Reacta-Link Wireless Presence RCS - Reacta-Control Wireless, Presence *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	43.84 W	CRI	80
Total flux	7008 lm	LOR	100%
Luminous efficacy	160 lm/W	ULOR	4%
		Total power	43.84 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	427 lm	LOR	100%
Luminous efficacy	142 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 58.50 in

Width: 2.76 in

Height: 2.76 in

Electric

System power: 46.84 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Adjustability

Fixed