

Product data sheet


FLEXBAR RECESSED - 16W (6W/M) - SECONDARY STRAIGHT - 2800MM - METALLISED REF - 4000K - EMERGENCY
EFXR16LSM
THORLUX LIGHTING



IP
20

Flexbar Recessed is an elegant recessed linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	3050 lm	LOR	100%
Luminous efficacy	161 lm/W	Total power	19 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 110.24 in
Width: 2.28 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 19 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 20