


# Product data sheet

LIGHT LINEAR DENVER 4 STREET AND AREA LUMINAIRES  
DE-20032-ME-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 100 km/h - Surge protection 10kV

## Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	81.7 W	CRI	80
Total flux	8030 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	81.7 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	81.7 W	CRI	80
Total flux	8030 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	81.7 W

## Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	81.7 W	CRI	80
Total flux	8030 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	81.7 W

**Mounting mode**

Standing / Bollard, Pole top mounted

**Shape and measurements**

Length: 76.18 in

Width: 5.91 in

Height: 3.54 in

Weight: 42 kg

**Adjustability**

Fixed

**Design**

Color of housing: Black, White, Silver gray

**Glare protection**

Glare protection: UGR < 19

**Electric**

System power: 245.1 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

**Protection**

IP: 65

IK: 08

Surface temperature: 40°C