Product data sheet

NEPTUN INDUSTRY LED 20000 PC-OPAL E IP66 21 830 / 1563X115X110MM ZASILANIE PRZELOTOWE 16A HT50
19.4330.5411.21


LUXIONA



IP 66 IK 10

Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate. Colour - RAL 9006 (grey). Dimensions: 1563 x 115 x 110 mm. Diffuser: PC (opalescent polycarbonate). The efficiency of the optical system is 85,34%. Beam angle: (C0-C180) / (C90-C270) - 120,4° / 99°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 15952,9 lm. Power of luminaire: 104,3 W. Luminaire's light efficiency: 153 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 20 (B10), 32 (B16), 25 (C10), 40 (C16). Operating temperature range: -40 ÷ 50° C. Protection degree: IP66. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



3 x LED

Nominal lamp power	34.767 W	LOR	52%
Lamp flux	6231 lm	Total flux	9802 lm
Luminous efficacy	179 lm/W	Total power	104.3 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.54 in
Width: 4.53 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 104.3 W
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -40...122°F