


Product data sheet

SL764+ PL MP S/C 2X39/41° 32W 940 BK-RAL9005
3115836
PERFORMANCE IN LIGHTING



Part number: 3115836. Serie: SL764+. Suspended, LED luminaire for indoor, comprising: Extruded aluminium profile housing, die-cast aluminium end caps, powder-coated. Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP). Streamlined, simple design with flush end caps. High-quality workmanship of profile connections for a perfect look. Direct / indirect light distribution. Through-wiring designed. Simple and convenient lighting installation. Interchangeable lighting inserts. Colour tolerance according to MacAdam 3 SDCM. Complete with steel suspension cable (1.5 m), transparent power cable and canopy. Continuous mounted options and many other configurations are available at www.light-performer.com. Product data | ETIM Group: EG000027. ETIM Class: EC001743. General information | Lampholder: LED. Lightsource lumen output [lm]: 5510. Luminaire lumen output [lm]: 4460. Luminaire wattage [W]: 32 W. Luminous efficacy [lm/W]: 139. CRI: 90. Colour temperature [K]: 4000. Colour / Finishing: BK-RAL9005 / Black RAL9005 / Textured. IP degree of protection: IP40. IK05 0.7J xx3. Protection class: I. Optic: S/C - Symmetric direct-indirect. Beam angle: 2 x 39°/41°. Net weight [kg]: 5.685. Overall length [mm]: 1132. Overall width [mm]: 44. Overall height [mm]: 66. Mechanical features | Shape: Rectangular. Housing material: Aluminium. Diffuser material: Transparent plastic. Glow wire test [°C]: 650 °C. Electrical features | Voltage type: AC. Input voltage [V AC]: 220/240. Input frequency [Hz]: 220-240V 50/60Hz. Power factor / COS Φ: 0.9. Input voltage [V DC]: 186/250. Inrush current [A/μs]: 31 / 175. C10 1.5 mm²: 23. C16 2.5 mm²: 38. B10 1.5 mm²: 14. B16 2.5 mm²: 23. Installation | Application area: PROFESSIONAL INDOOR. Mounting type: . Min. ambient temperature [°C]: 10. Max. ambient temperature [°C]: 40. Loop through. Light features | Lamps: 1. ILCOS: DSL. MacAdam: 3. Lumen maintenance: L80B10@50000h. Distribution of light emission: Direct/Indirect. DFF - Downward Flux Fraction [%]: 50. UFF - Upward Flux Fraction [%]: 50. UGR max.: 17.0. Certifications | CE certified. ENEC certified. EAC certified. UKCA certified. Mountable on normally inflammable surfaces.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	32 W	CRI	90
Total flux	4461 lm	LOR	100%
Luminous efficacy	139 lm/W	ULOR	78%
		Total power	32 W

Mounting mode

Pendant

Shape and measurements

Length: 1.73 in
Width: 44.57 in
Height: 2.60 in

Electric

System power: 32 W
Appliance Class: 0

Protection

IP: 40
IK: 05
Designation labels: CE, ENEC, F

Adjustability

Height adjustable

Design

Color of housing: Black