

Product data sheet


LIGHT SNIPER SQUARE
03.4603/QR-CBC 51/35W/10°24°38°60°
FLOS



IP
44


High performance luminaires for embedded installation for halogen lamps with dichroic reflector, metal halide reflector or LED lamps. They offer a high comfort due to the back visual position of light source. Body of the luminaire made of two bodies of injected aluminium. Square front ring made of steel sheet 1mm thick with white matt finish. It incorporates shielded cones made in zamak injection in three sets: black, matt gold and chrome. Fixed, tilt and wall-washers versions. Spreading lens made in opal tempered glass in halogen fixed and tilt versions. In wall-washer versions a distribution lens made of borosilicate is incorporated. IP44

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	1126 lm	LOR	38%
Luminous efficacy	12 lm/W	Total flux	425 lm
CCT	3000 K	Total power	35 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	1136 lm	LOR	58%
Luminous efficacy	19 lm/W	Total flux	661 lm
CCT	3000 K	Total power	35 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	1116 lm	LOR	61%
Luminous efficacy	19 lm/W	Total flux	681 lm
CCT	3000 K	Total power	35 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	902 lm	LOR	61%
Luminous efficacy	16 lm/W	Total flux	548 lm
CCT	3000 K	Total power	35 W
CRI	100		

Mounting mode

Ceiling recessed

Electric

System power: 35 W

Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.91 in

Protection

IP: 44

Adjustability

Fixed