
Product data sheet

TENTEC RECESSED LUMINAIRE, WALLWASHER
T26010-03 + 81030R23
SCHMITZ | WILA



Tentec Fluorescent Lamps TC-TEL(I) Recessed Luminaire, Light distribution direct, asymmetric Wallwasher-Downlight Product: T26010-03 Lite Optic: 81030R23 Lite Optic Additional wall oriented light focus with the use of a directional reflectorSatin matt finished, high quality pure aluminumSupporting frame whiteRetrofit Light Technique Mirror reflector made of corrosion and age resistant pure aluminium (Al99.8), silver polished and post anodised Luminaire housing Robust housing made of die-cast aluminium for preparation of WILA Liteoptics Lamp holder made of fire resistant plastic according to UL94V-O Operating and assembly technology Electronic ballast, static, with highest energy efficiency with label EEI A2 Separate EB Module with 380 mm connecting cable for simple mounting in restricted ceiling voids Fast connector clamp for 3 x 1,5 mm², optional through wiring possible MS-3 mounting technique for a tool free change of Liteoptics Threaded 3-point mounting for ceiling thicknesses 1-25 mm, via hollow wall box principle for a quick installation Relamping requires no tools Lamp Wattage: 1 x 42 W Luminaire Luminous Flux: 2260 Llm System Efficiency: 51 Llm/W Luminance γ ≥ 65°: --- Number Luminaires LZ: 0.06 Connector: plug-in terminal, 3 x 2.5 mm2 Reflector Size: R23 Diameter D: 255 mm Cut-out CO: 240 mm Installation Depth RD: 125 mm Total Weight: 1.1 kg Degree of Protection IP20 CE-Sign Total system: Protection class 1 Data record T26010-03+81030R23

Light output 1



1 x General service incandescent lamp

Nominal lamp power	42 W	LOR	70%
Lamp flux	3200 lm	Total flux	2255 lm
Luminous efficacy	51 lm/W	Total power	44 W
CCT	4000 K		
CRI	82		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.92 in
Diameter: 10.04 in

Adjustability

Fixed

Electric

System power: 44 W
Appliance Class: I

Protection

IP: 20