Product data sheet


X-LINE SLIGHT L-DOWN LED 1300 PLX E 21 830 LINE-S / L-568MM S-1,5M
19.4421.1111.21
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9006 (grey). Dimensions: 568 x 34 x 68 mm. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,50%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 1052,8 lm. Power of luminaire: 8,6 W. Luminaire's light efficiency: 122,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 23 (B10), 36 (B16), 35 (C10), 60 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	8.6 W	LOR	52%
Lamp flux	1404 lm	Total flux	736 lm
Luminous efficacy	163 lm/W	Total power	8.6 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 22.36 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 8.6 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F