

Product data sheet

BASIC CATEGORY


V1-U0-00006-21000-6500850 HCS IP65 8 W 8W 5000K

VARTON



• Robust rectangular luminaire • Material: Plastic housing, polycarbonate diffuser Application • Entrances • Lobbies • Corridors • Stairways Installation • Surface-mounted on the wall or ceiling Input voltage (AC, 50Hz), V: 220...240 AC frequency, Hz: 50 Flicker, %: 10 Climatic modification and category of placement: YXЛ1 Protection class: II Housing material: Plastic Mounting method: Surface mounting Ingress protection (IP): IP65 Impact resistance: IK10 Power factor: 0,85 <https://www.varton.ru/products/basic-kategoriya/zhkkh-ip65/zhkkh-8-vt/svetodiodnyy-svetilnik-varton-zhkkh-seriya-8-vt-ip65-224kh90kh52-mm-antivandalnyy-5000-k-1-20/>

Light output 1



1 x LED			
Nominal lamp power	8 W	LOR	100%
Lamp flux	900 lm	Total flux	900 lm
Luminous efficacy	112 lm/W	Total power	8 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.82 in

Width: 3.54 in

Height: 2.05 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 65