Product data sheet


LINA45-S 145S-5C1I-35GHM3/840, B
145S-5C1I-35GHM3/840
HALLA



IP 20


145S-5C1I-35GHM3/840, B Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1964 x 47 x 69 mm Type of installation: Suspended Distribution: Direct-indirect clear plexi Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	260 lm	LOR	100%
Luminous efficacy	173 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	78.7 W	CRI	80
Total flux	12090 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	78.7 W

Mounting mode

Pendant

Shape and measurements

Length: 1.85 in
Width: 77.32 in
Height: 2.72 in

Adjustability

Fixed

Electric

System power: 80.2 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20