

Product data sheet

RAX SURFACE 200 WHITE 3250LM 4000K RA>80 DALI PUSH DIM


5703821164320

SG ARMATUREN



Rax 200 Surface is designed for applications with solid ceilings and will reduce lighting costs without compromising the visual quality of indoor environments. The unique reflector design combined with the latest LED technology ensures high efficiency. Light distribution Direct Light technic LED 27W 4000K Ra>80 SDCM 2 L90/B10 >50,000 hrs at Ta=25°C Control/Dimming DALI Push Dim Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Spun aluminium Colour: White Optics: Aluminium Mounting/Connection Surface, Indoor Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED

Nominal lamp power

27 W

LOR

100%

Lamp flux

3250 lm

Total flux

3251 lm

Luminous efficacy

120 lm/W

Total power

27 W

CCT

4000 K

CRI

80

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.78 in

Width: 8.78 in

Height: 9.96 in

Adjustability

Fixed

Electric

System power: 27 W

Appliance Class: I

Protection

IP: 20