


# Product data sheet

SMART CAKE 160 IP55 LED GE 4000K FLOOD WHITE STRUC  
13004809  
MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


## Light output 1




1 x LED			
Nominal lamp power	36.3 W	LOR	85%
Lamp flux	4427 lm	Total flux	3779 lm
Luminous efficacy	104 lm/W	Total power	36.3 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	30.8 W	LOR	85%
Lamp flux	3828 lm	Total flux	3267 lm
Luminous efficacy	106 lm/W	Total power	30.8 W
CCT	4000 K		
CRI	90		




1 x LED			
Nominal lamp power	23.5 W	LOR	85%
Lamp flux	3084 lm	Total flux	2632 lm
Luminous efficacy	112 lm/W	Total power	23.5 W
CCT	4000 K		
CRI	90		




**1 x LED**

Nominal lamp power	16 W	LOR	85%
Lamp flux	2265 lm	Total flux	1933 lm
Luminous efficacy	121 lm/W	Total power	16 W
CCT	4000 K		
CRI	90		



**1 x LED**

Nominal lamp power	49.7 W	LOR	85%
Lamp flux	5725 lm	Total flux	4886 lm
Luminous efficacy	98 lm/W	Total power	49.7 W
CCT	4000 K		
CRI	90		



**1 x LED**

Nominal lamp power	42 W	LOR	85%
Lamp flux	4972 lm	Total flux	4244 lm
Luminous efficacy	101 lm/W	Total power	42 W
CCT	4000 K		
CRI	90		

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

**Adjustability**

Fixed

**Electric**

System power: 16-49.7 W

Appliance Class: II

**Protection**

IP: 55