

Product data sheet

AVENIDA LENS LED 35W 4200LM 4000K IP66 O21 - FOR BIKE PATHS GRAY II


130272.3L082.041

LUG



Park luminaire in modern form for LED light sources. Mounting: on pillar ø48/60/76mm, with mounting bracket (included) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0,088 m² Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, LLOC, twilight sensor, 10kV surge protection, NTC Other remarks: the pole is not part of the luminaire Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, residential, public spaces, playgrounds, promenade, residential area roads Type of optics: O21 - for bike paths

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	70
Total flux	4200 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	35 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 14.17 in

Width: 14.17 in

Height: 18.98 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 35 W

Controller: DALI

Appliance Class: II

Protection

IP: 66

IK: 10