


Product data sheet

SPOT VARIO 170 35 W 3000 K 24DEG WT
4058075104020
LEDVANCE



Recessed mounted spotlight, swivelable. Product features: Large faceted reflector for high light output. Beam angle: 24°. Rotation angle: 0°...350°, tilt angle: 0°...35°. Diameter of required ceiling cut out: 165...170 mm. Product benefits: Low flicker light thanks to special electronic control gear. High luminous efficacy. Die-cast aluminum housing for improved heat dissipation. Easy replacement of external driver thanks to plug with bayonet lock. Design matches the LEDVANCE Spot-, Down- and Tracklight luminaire family. Shallow mounting depth. Various options to highlight target areas. 5 years guarantee. Areas of application: Accent- and general lighting for all kind of salesrooms. Retail. Supermarkets. Shops, boutiques. Hotel rooms. Stairways. Corridors. Lobbies. Equipment / Accessories: Driver included. Safety advice: All electrical connections must be made by a qualified person.. Caution, risk of electric shock.. The luminaires are not suitable for covering with thermally insulated material..

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	35 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.06 in
Width: 7.80 in
Height: 7.09 in
Weight: 1.126 kg

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 35 W
Appliance Class: II

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...113°F