
Product data sheet

ALTIS 2KW R6 HQITS-S CL1 WI
96263375
THORN LIGHTING



A high performance discharge floodlight for 1 x 2000W HIT-DE OSS lamp. magnetic. Class I electrical, IP66. Body and frame: die-cast aluminium unpainted. Enclosure: 4mm thermally toughened glass. Stirrup fixed by single bolt through Ø22mm hole, or 105x17mm oblong hole, or by twin bolts through Ø15mm holes. Cable gland for 8 to 12mm cable. Aiming via integrated sights. Ideal for sports field and stadium lighting. Complete with ignitor box. Gear tray to be ordered separately. Lamp to be ordered separately. Total power: 2075 W Dimensions: 566 x 626 x 285 mm Weight: 14.25 kg Scx: 0.21 m²

Light output 1



1 x General service incandescent lamp

Nominal lamp power	2000 W	LOR	76%
Lamp flux	200000 lm	Total flux	151669 lm
Luminous efficacy	73 lm/W	Total power	2075 W
CCT	3000 K		
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.28 in
Width: 24.65 in
Height: 11.22 in
Weight: 14.3 kg

Design

Material impression: Aluminum

Electric

System power: 2075 W
Voltage: 380-415 V AC
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE, ENEC