

Product data sheet


ARTERA LED DALI 49W 6950LM 3000K IP66 O3 - FOR LOCAL ROADS GRAPHITE II
130355.3L032.020

LUG



Modern urban-park luminaire for LED light sources with multiple mounting options and distinctive design. In order to mount the luminaire, a suitable mounting bracket (accessories) must be ordered. High efficacy to 150 lm/W Mounting on pillar, on outriggers, with mounting brackets (on request). Body high pressure die-cast aluminum. Lateral Surface Wind Exposed 0.048 m². Power supply efficiency 90% Power 220-240V 50/60Hz Lifetime LED (L90) 100 000 h Available on request: LLOC, twilight sensor, 10kV surge protection, NTC, NEMA connector, ZHAGA connector, iBLOC controller Additional information: luminaires are not equipped with a tight connector. Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application:avenues, sidewalks, parks, residential, public spaces, Railway stations, facades, promenade, roads, local roads, town roads, residential area roads, parking areas, playgrounds. Type of optics: O3 - for local roads

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	49 W	CRI	70
Total flux	6950 lm	LOR	100%
Luminous efficacy	142 lm/W	Total power	49 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in

Width: 21.65 in

Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 49 W

Controller: DALI

Appliance Class: II

Protection

IP: 66

IK: 08