


Product data sheet

ALU-STANDARD

501022.004.1

RZB




IP
54

IK
03

Series: Alu-Standard LED Type of Protection: IP 54 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. With three M20x1.5 cable inlets. Cover: textured glass, frosted. "Clamp ring: stainless steel wire; screw mounting. When" mounted to a wall the three cable inlets must be pointing downwards. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 210, B 130, H 85 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 170lm System power: 8W Beam Angle: 153°/126° Unified Glare Ratio: 20,0 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 8 W | CRI | 80 |
| Total flux | 170 lm | LOR | 100% |
| Luminous efficacy | 21 lm/W | ULOR | 16% |
| | | Total power | 8 W |

Mounting mode

Wall mounted

Shape and measurements

Length: 5.12 in

Width: 8.27 in

Height: 3.35 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 54

IK: 03