Product data sheet


FLOODLIGHTS
V1-I0-70591-04L41-6515030 FL-PRO 150/200 W 150W 3000K
VARTON



IP 66 IK 08

Professional floodlight with a high quality lighting. Wide range of optics and CCT. Material: Cast aluminum body, acrylic optic, protective tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Floodlighting. Architectural. Outdoor areas. Industrial facilities. Warehouses. Input voltage (AC, 50Hz), V: 100...305 AC frequency, Hz: 50 Input voltage (DC), V: 145...430 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Height/depth, mm: 95 Length, mm: 507 Protection class: I Fire danger class: П-I,II,IIa,III Ingress protection (IP): IP66 Impact resistance: IK08 Width, mm: 339 Power factor: 0,95 https://www.varton.ru/products/prozhektory/fl-pro/fl-pro-150-200-vt/svetodiodnyy-svetilnik-varton-prozhektor-fl-pro-80-150-vt-3000-k-ral7045-muar/

Light output 1



1 x LED

Nominal lamp power	150 W	LOR	100%
Lamp flux	21200 lm	Total flux	21200 lm
Luminous efficacy	141 lm/W	Total power	150 W
CCT	3000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 19.96 in
Width: 13.35 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 150 W

Protection

IP: 66
IK: 08