


Product data sheet

UNI-BRIGHT MOON 180 CCT - BLACK - 2700K/3000K/4000K
 MN18014WBCCT
 PROLED (MBN GMBH)




Versatile LED surface mounted luminaire Black - diam 180 mm - opal plexiglass - 3CCT 2700K/3000K/4000K

Light output 1




1 x LED

Nominal lamp power	14 W	LOR	100%
Lamp flux	1300 lm	Total flux	1300 lm
Luminous efficacy	93 lm/W	Total power	14 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	14 W	LOR	100%
Lamp flux	1300 lm	Total flux	1300 lm
Luminous efficacy	93 lm/W	Total power	14 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	14 W	LOR	100%
Lamp flux	1300 lm	Total flux	1300 lm
Luminous efficacy	93 lm/W	Total power	14 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 14 W
 Appliance Class: I

Shape and measurements

Height: 1.38 in

Diameter: 7.09 in

Weight: 0.8 kg

Adjustability

Fixed

Protection

IP: 54

Other operating numbers

Ambient temperature range: 14...113°F