

# Product data sheet

DEECOS P MAXI  
911536.002.76  
RZB




IP  
20

IK  
06

Series: DEECOS P maxi Cylindrical pendant luminaire. Housing: die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel with magnetic attachment. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. Transparent suspension cable 2 m, can be shortened. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Decorative recessed suspension set available as accessory. Colour: traffic white, matt (RAL 9016) Diameter: 123 mm Height: 181 mm Suspension length: 2000 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 92 System power: 35 W Rated luminous flux: 4200 lm Beam angle Down: 12° Luminous efficiency: 120 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	90
Total flux	4200 lm	LOR	74%
Luminous efficacy	120 lm/W	ULOR	20%
		Total power	35 W

## Mounting mode

Pendant

## Shape and measurements

Height: 7.13 in  
Diameter: 4.84 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 35 W

## Protection

IP: 20  
IK: 06