


# Product data sheet

CALLISTO WALL GRAPHITE 100LM 2700K Ra>80 TRAILING EDGE DIMMING  
7021989230175  
SG ARMATUREN



Good little LED luminaire for walls and ceiling. For both outdoor and indoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, powder coating and 10-year corrosion warranty, glass diffuser. 33 cm in total height, KL II means that it can be mounted without earthing, direct 230 V with loopable quick clips. Light distribution Direct/Asymmetric Light technic LED (not exchangeable) 3W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK06 Energy and approvals CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 115, B16: 184, C10: 134, C16: 215

## Light output 1



1 x LED			
Nominal lamp power	3 W	LOR	100%
Lamp flux	100 lm	Total flux	100 lm
Luminous efficacy	33 lm/W	Total power	3 W
CCT	2700 K		
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 4.33 in  
Width: 1.06 in  
Height: 4.33 in

## Adjustability

Fixed

## Electric

System power: 3 W  
Appliance Class: II

## Protection

IP: 65  
IK: 06