Product data sheet


COLUMN LUMINAIRE RESIDENZA-2 C ZERO ASY17 16LED 2700K
88.00900.0V0XX + 99.20944.1V00X
HESS



IP 65


Illuminating column made of aluminium, consisting of top element and base element. Protective cover and luminaire glass made of clear PC glass. Light source sits on four aluminium rods. Cylindrical luminaire body made of cast aluminium. Diameter 200 mm. ULOR of 0%, complies with the Dark Sky Standard. Rods and internal parts uniformly painted, dark anthracite textured (similar to DB 703/Gris 2900 sablé). Total height of columns including luminaire 4600 mm

Light output 1




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2303 lm	Total flux	2303 lm
Luminous efficacy	114 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3895 lm	Total flux	3895 lm
Luminous efficacy	115 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3641 lm	Total flux	3641 lm
Luminous efficacy	115 lm/W	Total power	31.6 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3384 lm	Total flux	3384 lm
Luminous efficacy	115 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3121 lm	Total flux	3121 lm
Luminous efficacy	115 lm/W	Total power	27.1 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2579 lm	Total flux	2579 lm
Luminous efficacy	115 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2017 lm	Total flux	2017 lm
Luminous efficacy	112 lm/W	Total power	18 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1723 lm	Total flux	1723 lm
Luminous efficacy	110 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1424 lm	Total flux	1424 lm
Luminous efficacy	106 lm/W	Total power	13.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1113 lm	Total flux	1113 lm
Luminous efficacy	100 lm/W	Total power	11.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2853 lm	Total flux	2853 lm
Luminous efficacy	115 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 10.76 in
Width: 10.76 in
Height: 183.38 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65