


Product data sheet

JET 58 CYLINDRICAL BOLLARDS
JE-10581-T3-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 11.7 W | CRI | 80 |
| Total flux | 678 lm | LOR | 100% |
| Luminous efficacy | 58 lm/W | Total power | 11.7 W |

Light output 2 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 11.7 W | CRI | 80 |
| Total flux | 678 lm | LOR | 100% |
| Luminous efficacy | 58 lm/W | Total power | 11.7 W |

Mounting mode

Standing / Bollard

Shape and measurements

Height: 39.37 in
Diameter: 10.63 in
Weight: 7 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 23.4 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C