Product data sheet


HOME 502
221177.002.1
RZB



IP 20 IK 06

Series: Home 502 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 Hz Fitting galvanised sheet steel, with mounting screws. Housing plastic (PC). Diffuser plastic, opal (PC). Housing and diffuser permanently connected. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 200, H 48 Lamp: LED Life time: 35000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: EB Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 1100lm System power: 12W Beam Angle: 114° Number of fittings B10A: 16 Number of fittings B16A: 26 Number of fittings C10A: 27 Number of fittings C16A: 44 Inrush current: 23,2A Unified Glare Ratio: 25,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	80
Total flux	1100 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.89 in
Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 20
IK: 06