


Product data sheet

LOUI 50
925337.002
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: traffic white, matt (RAL;9016) Length: 1121;mm Width: 71;mm Height: 1.5;mm Cut-out length: 1128;mm Cut-out width: 60;mm Recess height: 100;mm Luminaire: recess height: 75;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28;W Rated luminous flux: 3100;lm Luminous efficiency: 111;lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	28 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 44.13 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 03