Product data sheet


FLEX50
FX50H-498401-HXXXO
EGLO



IP 20


pendant mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.62 W	CRI	80
Total flux	554 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	4.62 W

Mounting mode

Pendant

Shape and measurements

Length: 51.06 in
Width: 51.06 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 36.96 W

Protection

IP: 20
Designation labels: CE