


Product data sheet

ECO0 - 20W - 1370LM - TYPE II
0660012A-830
ARCLUCE



IP DEGREE : IP66 IK RATING : IK07 ELECTRICAL INSULATION CLASS: I LUMINAIRE Die-cast aluminium body (EN 47100). Polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing or optical polymer lenses. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3. INSTALLATION Galvanized and painted steel bracket. M20 technopolymer cable gland with anti-condensation valve. Supplied with power cable (0.5m).

Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1370 lm	Total flux	1367 lm
Luminous efficacy	68 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 5.63 in
Width: 3.27 in
Height: 1.97 in

Adjustability

Free

Electric

System power: 20 W

Protection

IP: 66
IK: 07