


Product data sheet

ALBERTSLUND MAXI POST LED 2700K 55W CLO
91742-1001
LOUIS POULSEN



Albertslund Maxi LED Design : Jens Møller-Jensen Light concept : The fixture emits symmetrical glare-free light directed downwards. The top shade helps direct the light downwards and prevent light from being emitted upwards. The white painted reflectors result in diffuse and comfortable light distribution. Finish: Aluminium coloured with textured surface, graphite with textured surface or grey, powder coated. Material: Top shade: Form pressed glass fibre. Enclosure: Injection moulded clear polycarbonate. Anti glare ring: Injection moulded polycarbonate. Base: Die cast aluminium. Struts: Aluminium. Mounting: Pole dimension: Ø 76mm. Installation cable: 5 m 3x1,5mm² + 2x0,5mm² (Class I) or 5 m 2x1,5mm² + 2x0,5mm² (Class II). LED driver: In fixture head. Weight: Max. 19 kg Class: Ingress protection IP66. Electric shock protection I w. ground, II w/o ground.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	55 W	CRI	80
Total flux	4609 lm	LOR	69%
Luminous efficacy	84 lm/W	Total power	55 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 25.98 in

Diameter: 34.65 in

Adjustability

Fixed

Electric

System power: 55 W

Appliance Class: II

Protection

IP: 66

IK: 10