


Product data sheet


SINUS SURFACE LIGHT WHITE 1530MM
R33A153-9016E1940L1S
PLANLICHT



IP
40


low output LED 4000K CRI 90 57W 6448lm <https://katalog.planlicht.com/en-us/fam-sinus/>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.12 W	CRI	90
Total flux	806 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	7.12 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 60.24 in

Width: 60.24 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 57 W

Protection

IP: 40