


Product data sheet

GUSTAV I (WALL FITTING)
9.744.5547.07
LEIPZIGER LEUCHTEN



Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge
Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	54%
Lamp flux	3200 lm	ULOR	11%
Luminous efficacy	37 lm/W	Total flux	1717 lm
CCT	2899 K	Total power	46 W
CRI	90		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 46 W
Ballast: ECG
Suitable for feed-through wiring

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F