

Product data sheet


METROPOLI 2XG24_STRUCTURE POLISHED
D20/27.4V
LUCEPLAN



IP
20


Sobrio e impeccabile, il telaio in alluminio pressofuso contiene il diffusore e dispone di una serie di ottiche intercambiabili che permette di utilizzare a scelta lampadine alogene o fluorescenti, Metropoli viene ora proposta con nuove sorgenti LED per una maggiore efficienza luminosa. Il diffusore è in vetro stampato prismaticizzato o policarbonato opalino (tenuta stagna).

Light output 1




2 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	G24D_3
Lamp flux	1800 lm	LOR	55%
Luminous efficacy	20 lm/W	Total flux	1981 lm
CCT	3000 K	Total power	100 W
CRI	85		




2 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	G24D-2
Lamp flux	1200 lm	LOR	55%
Luminous efficacy	13 lm/W	Total flux	1321 lm
CCT	3000 K	Total power	100 W
CRI	85		



2 x Halogen low voltage lamp without reflector

Nominal lamp power	80 W	Socket	R7S
Lamp flux	1400 lm	LOR	55%
Luminous efficacy	15 lm/W	Total flux	1541 lm
CCT	3000 K	Total power	100 W
CRI	99		



2 x Halogen low voltage lamp without reflector

Nominal lamp power	70 W	Socket	E27
Lamp flux	1200 lm	LOR	55%
Luminous efficacy	13 lm/W	Total flux	1321 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.16 in

Width: 10.62 in

Height: 10.57 in

Adjustability

Fixed

Electric

System power: 100 W

Protection

IP: 20