


# Product data sheet

DIRO SBL L 930  
11437 9300  
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named DIRO SBL L 930, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 208 mm is needed and a min. depth for recessing of 70 mm. This luminaire is equipped with LED cluster 18,5W / CRI>90 / 3000K / 2288lm with build-in driver to operate on a voltage of 100-240V / 50-60Hz. Not dimmable Light distributor: opal diffuser.

## Light output 1



1 x LED			
Nominal lamp power	21.5 W	LOR	73%
Lamp flux	2288 lm	Total flux	1664 lm
Luminous efficacy	106 lm/W	Total power	21.5 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	21.5 W	LOR	73%
Lamp flux	2288 lm	Total flux	1664 lm
Luminous efficacy	106 lm/W	Total power	21.5 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.08 in  
Diameter: 8.58 in  
Weight: 0.8 kg

## Electric

System power: 21.5 W  
Appliance Class: I

## Protection

IP: 20  
Designation labels: CE