

# Product data sheet


SAFELITE 20M,MNM,IP65,100LM,3H,CGL+,2X2X2,5MM²  
SL2-65D3D-CGL  
EATON EMERGENCY LIGHTING



IP  
65


• Compact self-contained luminaire for all applications (Escape route, Anti-panic, Exit sign) • IP42 & IP65 versions with same dimensions • One product throughout installation for same look and feel across the building • EN compliance • Luminaire suitable for maintained and non maintained mode • Accessories available for a better integration in all buildings • Easily installed as retro fit due to good performance ensuring scheme compliance • 3h Duration • Latest generation LEDs with high lumen/watt ratio • Manual test via magnet • Delivered with a set 3 adhesive exit pictograms (L, R, D)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.2 W	CRI	80
Total flux	100 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	4.2 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.2 W	CRI	80
Total flux	100 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	4.2 W

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 10.63 in

Width: 4.72 in

Height: 1.97 in

### Adjustability

Fixed

### Electric

System power: 8.4 W

### Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

### Protection

IP: 65