


# Product data sheet

CRUISER 2 LED ED 22600LM 4000K IP66 110° GRAY  
090432.5L06.013  
LUG



Industrial luminaire for LED light sources. Mounting: surface mounted, in the ceiling, with mounting frame (sold separately), suspended, on chains (on request), for hanging on a cable, with special mounting bracket (on request) Body: high pressure die-cast aluminum Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Additional information: Ball impact resistance. The possibility of using one or more power supplies in the luminaire. Warranty: 5 years Application: warehouses, logistics centers, industrial facilities, sport facilities, roofing, outdoor installation without roof on special request (index extension: .985)

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	174 W	CRI	80
Total flux	22600 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	174 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 20.28 in  
Width: 13.58 in  
Height: 3.54 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 174 W  
Appliance Class: I

## Protection

IP: 66  
IK: 07  
Resistant to impact of balls