

Product data sheet

SANTOS QUADRAT
311881.005
RZB



IP
20

Series: Santos Quadrat Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, white, powder-coated. Diffuser fastening: spring system. Diffuser: opal glass, domed, frosted. Decorative frame: metal. Available Colours: brass Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 310, B 310, H 95 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 740lm System power: 10W Beam Angle: 114° Number of fittings B10A: 17 Number of fittings B16A: 27 Number of fittings C10A: 28 Number of fittings C16A: 46 Inrush current: 27A Unified Glare Ratio: 18,7 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	740 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	2%
		Total power	10 W

Mounting mode

Ceiling mounted

Electric

System power: 10 W

Shape and measurements

Length: 12.20 in

Width: 12.20 in

Height: 3.74 in

Protection

IP: 20

Adjustability

Fixed