Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I2-70210-03G02-6501665 STRONG 2.0 1,2 M 16W 6500K OPAL
VARTON



IP 65

Industrial linear luminaire in a classic form factor. Material: Impact-resistant, self-extinguishing ABS housing, polycarbonate diffuser. Installation:Suspended and surface-mounted with stainless steel mounting brackets (included in package). Application: Administrative facilities, Industrial facilities, Warehouses. Power factor: 0,95 Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Input voltage (DC), V: 176...264 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK10 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/strong-2-0/strong-2-0-1-2m/svetodiodnyy-svetilnik-varton-strong-2-0-promyshlennyy-16-vt-6500-k-1242kh90kh68-mm-klass-zashchity-_8/

Light output 1



1 x LED

Nominal lamp power	16 W	LOR	100%
Lamp flux	2100 lm	Total flux	2100 lm
Luminous efficacy	131 lm/W	Total power	16 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.90 in
Width: 3.54 in
Height: 2.68 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 65