

Product data sheet


URBANO TWILIGHT LED 103W 12250LM 4000K IP66 O2 - FOR EXPRESS ROADS REGULATION 0° ... +15° GRAY I
130192.5L05.12.986

LUG



Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. Mounting: on pillar $\varnothing 60/76\text{mm}$, on outriggers $\varnothing 60/76\text{mm}$ Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m^2 Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, 10kV surge protection, NTC Additional information: Tilt adjustment: 5° , knife switch (for protection class I), access to the driver chamber without the use of tools. The possibility of using one or more power supplies in the luminaire. Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting Type of optics: O2 - for express roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	103 W	CRI	110
Total flux	12250 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	103 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.74 in

Width: 11.61 in

Height: 8.54 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 103 W

Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor

Protection

IP: 66

IK: 08