Product data sheet


ZAAB 2 CLUSTER COLUMN PROJECTORS ZA-20011-M-W40

LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K, 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear installed in the spigot cover post top

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Light output 3 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Light output 4 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Light output 5 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Light output 6 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3665 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	39.3 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 216.54 in Diameter: 29.37 in Weight: 43.8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 235.8 W Voltage: 230 V AC Ballast: ECG Controller: Dimmable 1..10V, DALI Appliance Class: I

Protection

IP: 66 IK: 07 Surface temperature: 40°C