Product data sheet


LUCAS X (WALL FITTING BEADED) 9.833.3066.16

LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR			

Norminal lamp power	125 VV	LUN	03 /0
Lamp flux	6800 lm	ULOR	2%
Luminous efficacy	41 lm/W	Total flux	5637 lm
CCT	3400 K	Total power	137 W
CRI	54		

$K K \rightarrow K X$	\checkmark
	9
	\mathbb{Z}
XATS	

ury vapour lamp		
80 W	LOR	83%
4000 lm	ULOR	2%
37 lm/W	Total flux	3316 lm
3400 K	Total power	89 W
54		
	80 W 4000 lm 37 lm/W 3400 K	80 WLOR4000 lmULOR37 lm/WTotal flux3400 KTotal power

Mounting mode Wall mounted Shape and measurements Height: 22.44 in

Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White

Electric

System power: 89-137 W Ballast: ECG

Protection

IP: 55 Designation labels: CE

Other operating numbers

Ambient temperature range: 1...95°F

83%