Product data sheet


LED DOWNLIGHTS
V1-RF-70111-10000-6500830 DL-01 11 W 8W 3000K
VARTON



IP 65 IK 08

Classic dust-tight downlight. Paintable in any RAL color. Application: healthcare, offices, commercial spaces, hospitality (restaurants, hotels, coffee bars), retail spaces. Installation: recessed into plasterboard, stretch or suspended ceilings. Input voltage (AC, 50Hz): 198...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Built-in Ingress protection (IP): IP65 Impact resistance: IK08 https://www.varton.ru/products/daunlayty/dl-01-rus/dl-01-rus-pro-100/svetodiodnyy-svetilnik-varton-dl-01-pro-100-mm-8-vt-3000-k-kruglyy-vstraivaemyy-120kh49-mm-ip65-40-r_3/

Light output 1



1 x LED

Nominal lamp power	8 W	LOR	100%
Lamp flux	720 lm	Total flux	720 lm
Luminous efficacy	90 lm/W	Total power	8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 1.93 in
Diameter: 4.72 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 65
IK: 08