



Product data sheet

LOUI 50
925341.002.76
RZB



Series: LESS IS MORE 50;system Einbaueckmodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: traffic white, matt (RAL9016) Length: 600;mm Width: 600;mm Height: 1.5;mm Cut-out length: 610;mm Cut-out width: 610;mm Recess height: 100;mm Luminaire: recess height: 75;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28;W Rated luminous flux: 2850;lm Luminous efficiency: 102;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	2850 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	28 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 03