
Product data sheet

RESCLITE PRO MSC ANT HC E1D WH IP65
42185774
ZUMTOBEL



LED emergency luminaire for antipanic lighting with min. 0,5 lux acc. to EN 1838; high ceilings (HC) version for high ceiling heights > 7 metres; 2 high power LEDs, neutral white 4,000 K; lens of polycarbonate; optimum thermal management via heat sink; Ceiling surface-mounted luminaire; white; Luminaire with local battery supply for 1 hr. emergency lighting in maintained or non-maintained mode, with automatic test (auto-test) via the luminaire, optional central monitoring via DALI, display of luminaire status via status LED; NFC interface for addressing, configuration and maintenance via PROset Pen (article no.: 22170290) or PROset app; non-maintained and maintained mode settable via jumper and NFC interface, ; Luminaire with ball-proof protection; Protection type IP65; SC1; Luminaire wired with halogen-free leads and contains no silicone; Plug-in terminals for through-wiring up to 2.5mm²; Impact strength: IK04; Dimensions: 200 x 145 x 64 mm; weight: 1.05 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.7 W	CRI	99
Total flux	295 lm	LOR	100%
Luminous efficacy	44 lm/W	Total power	6.7 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.87 in
Width: 5.71 in
Height: 2.52 in
Weight: 1.1 kg

Design

Material impression: Plastic
Color of housing: White

Electric

System power: 6.7 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 65
IK: 04
Designation labels: CE, ENEC