


Product data sheet

KOMBIC 100 RO 2500 IP43 WFL 840 DA W/W
K11RO2540WF840DWW
LAMP



Adjustable recessed downlight model KOMBIC 100 RO 2500 from the brand LAMP. Aluminum injection frame and R-PC FR WHITE TM recycled polycarbonate reflector with bromine-free flame retardant. Flammability degree V0 according to UL94. Interior reflector finished in white. Adjustable luminaire +/-20° with wide flood optics for greater efficiency and control of light distribution and reduction of UGR<19 glare. Aluminum injection heat sink with cataphoresis treatment for greater thermal stability. COB LED, with 4000K color temperature with CRI90. DALI-2 electronic equipment included. With an IP43 degree of protection. Insulation class II. Photobiological safety group 0. Hours of life: >100.000 L90 B10. Finished in black and white.

Light output 1



1 x LED			
Nominal lamp power	19.8 W	LOR	100%
Lamp flux	1802 lm	Total flux	1800 lm
Luminous efficacy	91 lm/W	Total power	19.8 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.15 in
Diameter: 5.51 in

Adjustability

Free

Electric

System power: 19.8 W
Appliance Class: II

Protection

IP: 43