


Product data sheet

PRO-STRADA MAXI, 66LEDS OPTIEK 5
41366X4X
PROLUMIA




Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	73.5 W	LOR	100%
Lamp flux	10000 lm	Total flux	10000 lm
Luminous efficacy	136 lm/W	Total power	73.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	77.6 W	LOR	100%
Lamp flux	10000 lm	Total flux	10000 lm
Luminous efficacy	129 lm/W	Total power	77.6 W
CCT	3000 K		
CRI	80		




1 x LED


Nominal lamp power	67.6 W	LOR	100%
Lamp flux	9200 lm	Total flux	9200 lm
Luminous efficacy	136 lm/W	Total power	67.6 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	71.4 W	LOR	100%
Lamp flux	9200 lm	Total flux	9200 lm
Luminous efficacy	129 lm/W	Total power	71.4 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	97 W	LOR	100%
Lamp flux	12500 lm	Total flux	12500 lm
Luminous efficacy	129 lm/W	Total power	97 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	85.4 W	LOR	100%
Lamp flux	11000 lm	Total flux	11000 lm
Luminous efficacy	129 lm/W	Total power	85.4 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	80.8 W	LOR	100%
Lamp flux	11000 lm	Total flux	11000 lm
Luminous efficacy	136 lm/W	Total power	80.8 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	91.9 W	LOR	100%
Lamp flux	12500 lm	Total flux	12500 lm
Luminous efficacy	136 lm/W	Total power	91.9 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 26.54 in

Width: 12.09 in

Height: 4.80 in

Electric

System power: 67.6-97 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC