


# Product data sheet

3-PH TRACK LIGHT FOCUSABLE, 42W, 20°-70°, WHITE MATT, 4000K, CRI92, DALI DIMMABLE  
116110  
ISOLED



DALI HV LED Track light, focusable, 42W, 20°-70°, white matt, 4000K, CRI92, DALI dimmable | Dimensioned power: 42 W | Effective power: 42 W | Energy efficiency class: D (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Surface color: white | Protection class: IP20 | Suitable for indoor use only | Allowable ambient Temperatures: -10° - 40° C | Diameter: 86 mm | Beam Angle: 20° - 70° Min-Max | Color Temperature: 4000K | Color rendering index: 92 (Ra 1-8) | Luminous flux: 5200 lm | DALI dimmable | Useful life: 68000 h (L80|B50) | Warranty: 5 years | | FABRICATION: ISOLED 116110

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 42 W     | LOR         | 100%    |
| Lamp flux          | 5200 lm  | Total flux  | 5199 lm |
| Luminous efficacy  | 124 lm/W | Total power | 42 W    |
| CCT                | 4000 K   |             |         |
| CRI                | 92       |             |         |

## Mounting mode

Ceiling mounted, Contact rail, Contact rail

## Shape and measurements

Height: 4.72 in  
Diameter: 3.39 in

## Adjustability

Rotatable, Tilttable

## Design

Material impression: Aluminum  
Color of housing: White

## Electric

System power: 42 W  
Ballast: ECG  
Controller: DALI

## Protection

IP: 20  
Designation labels: CE

## Other operating numbers

Ambient temperature range: 14...104°F