
Product data sheet


RECHTECK SEILPENDEL
671359.002.1.89
RZB



IP 44 IK 03


Series: RECHTECK Rectangular pendant luminaire in classic design. For escape route identification. Housing: aluminium, with plastic corner connectors. Display panels: plastic, opal, with motifs on one side/on both sides. Pendant luminaires (suspension provided on site) ready for connection to two suspension cables or chains. Driver integrated. Suitable for connection to central battery systems. With AC Control monitoring module for LUXIFAIR central battery units. Please indicate legend number when placing your order! Colour: traffic white, matt (RAL 9016) Length: 250 mm Width: 125 mm Height: 140 mm Weight: 1.4 kg Operating mode: maintained power mode Viewing Distance: 21 m Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 70 System power: 4.5 W Rated luminous flux: 100 lm Luminous flux, emergency: 100 lm System power, emergency: 4.5 W Control gear: Regulated power supply Protection class: I Type of protection: IP 44

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.5 W	CRI	70
Total flux	100 lm	LOR	100%
Luminous efficacy	22 lm/W	ULOR	28%
		Total power	4.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.5 W	CRI	70
Total flux	100 lm	LOR	100%
Luminous efficacy	22 lm/W	ULOR	28%
		Total power	4.5 W

Mounting mode

Pendant

Shape and measurements

Length: 4.92 in
Width: 9.84 in
Height: 5.51 in

Electric

System power: 9 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Design

Color of housing: White

Protection

IP: 44

IK: 03