


# Product data sheet

ECO-PANEL BL 595X595 34W


40000171

PROLUMIA




Light source: SMD 2835 LED Beam angle: 120° Color temperature: Switchable 3000K, 4000K en (and) 6000K Light output: Respectively 4400Lm, 4600Lm en (and) 4400Lm Color rendering index: Ra>80 Operating temperature: -20°C - +50°C Rated life hours: >50.000 (>50,000) LED current: 900mA Input: 220-240V, 50-60Hz Power factor: >0,95 (>0.95) Power consumption (driverincluded): 32 W Electrical safety class: Class II Driver: Various drivers, dimmable or not, can be ordered separately with or without power cord.

## Light output 1




### 1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4600 lm	Total flux	4600 lm
Luminous efficacy	135 lm/W	Total power	34 W
CCT	6500 K		
CRI	80		



### 1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4600 lm	Total flux	4600 lm
Luminous efficacy	135 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		



### 1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4600 lm	Total flux	4600 lm
Luminous efficacy	135 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 34 W

Appliance Class: 0

### Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 1.26 in

### Protection

IP: 20

Designation labels: CE