Product data sheet

LDA3B LED 3 1/2 INCH ADJUSTABLE/SLOPE DOWNLIGHT LDA3B02R409040D010-E3AA20G-30DEG

COOPER LIGHTING








Distributions: 10° - 70°; Optic holds 2 lens media, Lockable 365° rotation and 45° tilt holds any aiming position, Downlight, accent, and pinhole reflectors;, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 250, 700, 1000, 1300, 1800 and 2300, Excellent light control and low aperture brightness, Wavelinx and DLVP connected systems; 5-year warranty, Plaster lathing ring accessory offered for flush reflector transition

Light output 1 (integrated)



| Lamp type | LED | CCT | 4000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 5 W | CRI | 90 |
| Total flux | 248 lm | LOR | 100% |
| Luminous efficacy | 50 lm/W | Total power | 5 W |

Mounting mode

Pole top mounted

Shape and measurements

Height: 0.39 in Diameter: 3.50 in

Adjustability

Fixed

Electric

System power: 5 W

Protection

IP: 47