


Product data sheet

BERYL SURFACE NEW LED K-2/L2 3600 E 04 840
19.4039.1221.04
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: 341 x 167 x 192 mm. Diffuser: transparent glass. Beam angle: (C0-C180) / (C90-C270) - 39° / 39,2°. Light source type: LED. Colour of the light 4000 K. SDCM=2. CRI80. Lifetime of LED sources: 86000 (1) / 100000 (2) / 100000 (3) h L90/B10 (1) / L80/B10 (2) / L70/B10 (3). Luminaire luminous flux: 6221 lm. Power of luminaire: 51 W. Luminaire's light efficiency: 122 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 19 (B10), 31 (B16), 32 (C10), 52 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



2 x LED			
Nominal lamp power	25.5 W	LOR	83%
Lamp flux	4305 lm	Total flux	7186 lm
Luminous efficacy	169 lm/W	Total power	51 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.43 in
Width: 6.57 in
Height: 7.56 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black

Glare protection

Glare protection: UGR < 19

Electric

System power: 51 W
Appliance Class: I

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F