

Product data sheet


DOWNLIGHTS - COMFORT EVO 3000K
ACOM1/1 + ACOM/TR/W/1 + AHUEMKIT/LI (13W 3000K)
ANSELL LIGHTING



IP
44


ACOM1/1 + ACOM/TR/W/1 + AHUEMKIT/LI Comfort Evo • Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications • Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM*/1), offering great customisation and product upgradability • Deep cut-off angle for glare control and comfort • CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire • Downlight design allows installation into existing hole cut-outs of 210mm • Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities • Polycarbonate housing with unique thermal management for durability and optimum lifespan • Dimmable and Emergency options, standard and Self-Test Emergency available using the Hawk Kit Emergency Pack • LED lifespan L80 60,000 hours • Suitable for internal use only • 5 Year Product Warranty • IP44

Light output 1 (emergency)



1 x LED			
Nominal lamp power	3 W	LOR	100%
Lamp flux	290 lm	ULOR	19%
Luminous efficacy	97 lm/W	Total flux	290 lm
CCT	3000 K	Total power	3 W
CRI	70		

Light output 2



1 x LED			
Nominal lamp power	13.11 W	LOR	100%
Lamp flux	1622 lm	ULOR	19%
Luminous efficacy	124 lm/W	Total flux	1622 lm
CCT	3000 K	Total power	13.11 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in
Diameter: 9.06 in

Electric

System power: 16.11 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Design

Designer: Dominic Harkness

Protection

IP: 44